

Compressore Monocilindrico 48V DC

Interamente in metallo e montato su cuscinetti a sfera, garantisce prestazioni professionali con il minimo ingombro.
motore con scheda antidisturbo ai campi elettromagnetici



One Cylinder Compressor 48V DC

All-metal construction, assembled in ball bearings, ensures professional performances with minimum sizes.
motor with cardto the electromagnetic fields

CODICE :GRU48CC10



DATI TECNICI

Cilindrata	cmc 10				
Giri/minuto	2800				
	l/min.	cfm		bar	psi
Aria Aspirata/Aria Resa	30/21	0.72	a	2	29
	27/12	0.41	a	6	87
	29/8	0.27	a	8	116
Pressione max	8 bar				
Assorbimento Max	Amp. 3.6				
Potenza media assorbita	Watt 172				
Classe di protezione	IP 45				
Classe di servizio	S 3				
Rumorosità	Db 68				
Dimensioni compressore	Cm 15.6 x 6.5 x h13.8				
Peso compressore	Kg 1.5				

Si raccomanda un uso a ciclo intervallato Servizio S3



TECHNICAL DATA

Swept	cmc 10				
Rpm	2800				
	l/min.	cfm		bar	psi
Air Displacement/Air Delivery	30/21	0.72	at	2	29
	27/12	0.41	at	6	87
	29/8	0.27	at	8	116
Max pressure	8 bar				
Max Amp. absorption	Amp 3.6				
Average power absorption	Watt 172				
Protection class	IP 45				
Service class	S 3				
Noise level	Db 68				
Compressor dimensions	Cm 15.6 x 6.5 x h13.8				
Compressor weight	Kg1.5				

Only intermittent working Service S3

I dati sono suscettibili di modifiche senza preavviso - The company reserves the right to change any element without notice.

-ALCUNE VERSIONI / SOME MODELS-



GRU48CC10DIR 21x8xh13.8 Kg.2



KITSERLT1 Kg.3