

Compressore Bicilindrico 230V AC

Interamente in metallo e montato su cuscinetti a sfera, garantisce prestazioni professionali con il minimo ingombro.

**Two Cylinder Compressor 230V AC**

All-metal construction, assembled in ball bearings, ensures professional performances with minimum sizes.

CODICE :GRU230BCC40

**DATI TECNICI**

Cilindrata	cmc 40				
Giri/minuto	2800				
	l/min.	cfm		bar	psi
Aria Aspirata/Aria Resa	112/100	3.53	a	2	29
	107/86	3.03	a	6	87
	106/77	2.74	a	8	116
Pressione max 12 bar				12	174
Assorbimento Max	Amp 3.2				
Potenza media assorbita	Watt 350				
Classe di protezione	F				
Classe di servizio	S 3				
Rumorosità	Db 68				
Dimensioni compressore	Cm 36 x 11.5 x h17				
Peso compressore	Kg 5.2				

Con protezione termica salva motore

Si raccomanda un uso a ciclo intervallato

**TECHNICAL DATA**

Swept	cmc 40				
Rpm	2800				
	l/min.	cfm		bar	psi
Air Displacement/Air Delivery	112/100	3.53	at	2	29
	107/86	3.03	at	6	87
	106/77	2.74	at	8	116
Max pressure 12 bar				12	174
Max Amp. absorption	Amp 3.2				
Average power absorption	Watt 350				
Protection class	F				
Service class	S 3				
Noise level	Db 68				
Compressor dimensions	Cm 36 x 11.5 x h17				
Compressor weight	Kg 5.2				

With thermal protection motor

Only intermittent working

I dati sono suscettibili di modifiche senza preavviso - The company reserves the right to change any element without notice.

-ALCUNE VERSIONI / SOME MODELS-



ELECOM230BCLT5

44 x 14 x h34 Kg.10



ELECOM230BCLT5VAL

58 x 22 x h41 Kg.11



VALGRU230BCC40CH

53 x 29 x h27 Kg.8